



Asserta Mini Sounder

The most compact sounder in the Asserta Range, the Mini is a rugged unit with high IP rating. Suitable for use in harsh environments, its low current consumption makes it ideal as a general signalling device in industrial applications. The Mini is also available with a tamper switch (*supplied as separate module*) for secure applications. Any interference with the unit can signal an alarm to a security panel.



Technical Specification

Voltage	9 - 60Vdc 110 - 230Vac
Current	13mA @ 24Vdc (Typical Tone 3) 20mA @ 230Vac (Typical Tone 3)
Sound Output	105dB (Typical Tone 3)
Tones	32
Alarm Stages	2
Monitoring	Reverse Polarity (dc version)
Temperature	- 25°C to + 70°C
Protection	IP66
Construction	ABS
Weight	0.30Kg (dc version) 0.36Kg (mains version)
Colour	Red or grey



Features

- 32 tones
- Wide operating voltage
- IP66 protection
- Compact enclosure

Benefits

- Ideal for all general signalling applications
- Adaptable to all types of installation
- Suitable for harsh environments
- Can be used even in cramped spaces

Reference

AS/N/S/9-60V/R
AS/N/S/9-60V/G
AS/N/110-230/R
AS/N/SV/S/110-230V/G
AS/M/S/115-230/G
AS/S/115-230/G/120

Catalogue No.

7061154FUL-0105
7092269FUL-0146
7063134FULL-0155
7092268FUL-0145
7092267FUL-0144
7092274FUL-0151

Description

Asserta Mini Sounder, Red, 9 to 60Vdc
Asserta Mini Sounder, Grey, 9 to 60Vdc
Asserta Mini Sounder, Red, 110 to 230Vac
Asserta Mini Sounder, Grey, 110 to 230Vac
Asserta Mini Sounder, Grey, 115 to 230Vac
Asserta Mini Sounder, Grey, 115 to 230Vac